IN THE CLAIMS

The listing of claims will replace all prior version, and listing of claims in the application:

Claim 1 (cancelled)

- 2. (Currently Amended) A mailing form for facilitating a mailing of a document, comprising:
 - a bottom ply of the mailing form with a first side and a second side;
- a top ply of the mailing form with a first side and a second side, wherein the second side of the top ply is located over and facing the first side of the bottom ply:
- an adhesive interspersed between at least a portion of the first side of the bottom ply and at least a portion of the second side of the top ply;
- a removable portion of the <u>bottomtep</u> ply extending over the <u>firstsecond</u> side of the top ply, such that removal of the removable portion exposes the adhesive;
- document information printed on at least a portion of the <u>firstseeond</u> side of the topbettem ply;
- a vertical fold line for folding the mailing form after the removable portion of bottomtep ply has been removed away from the topbettem ply, the adhesive securing the mailing form when folded along the vertical fold line;
- a horizontal strip located on the <u>secondfiret</u> side of the <u>top</u>bettem ply, the horizontal strip including adhesive that is exposed after the mailing form is folded along the vertical fold line;
- a horizontal fold line for folding the mailing form that has been folded along the vertical fold line, the adhesive of the horizontal strip securing the mailing form when folded along the horizontal fold line: and
- a first perforation along a top margin of the top ply and the bottom ply_i, wherein when the mailing form is in folder configuration, the document information is firmly situated within the mailing form; and

Appl. No. 10/740,071 Docket No. 542-P0035

Reply to Office Action of August 3, 2007

a second perforation along the bottom margin of the top ply and the bottom ply, such that the first perforation and the second perforation can be torn when the mailing form is in

folder configuration, such that the mailing form can be unfolded along the horizontal fold line.

3. (Cancelled)

4. (Previously Presented) The mailing form of claim 3, wherein the first side of the bottom ply

includes a releasable substrate.

5. (Currently Amended) The mailing form of claim 3, wherein when the removable portion of

the bottomtop ply is removed, a horizontal strip of the topbottom ply located on a first portion

of the topbottom ply is removed.

6. (Previously Presented) The mailing form of claim 3, wherein the document is at least one

of:

a letter:

a registered mail;

a certified mail receipt;

a certified mail postcard;

a notice: and

an announcement.

7. (Original) The mailing form of claim 3, wherein the mailing form is adapted for printing in a

single pass through a sheet-fed, simplex, non-impact printer.

8. (Previously Presented) The mailing form of claim 3, wherein the second side of the bottom

ply includes variable information.

9. (Original) The mailing form of claim 8, wherein the variable information includes a sender

address, a recipient address and postage indicia.

4 of 9

Appl. No. 10/740,071 Docket No. 542-P0035 Reply to Office Action of August 3, 2007

- 10. (Original) The mailing form of claim 8, wherein the variable information is printed in an upward-facing orientation.
- 11. (Original) The mailing form of claim 8, wherein the variable information is printed in a downward-facing orientation.
- 12. (Currently Amended) The mailing form of claim 3, further comprising:

a third perforation in a vertical orientation along a right margin of the top ply and the bottom plythe first side of the mailing form, wherein the third perforation may be torn to produce a strip from the first side of the mailing form, the strip being used as a mail receipt.

- 13. (Original) The mailing form of claim 12, wherein the mailing form is a United States Postal Service Form 3811 and the strip is a United States Postal Service Form 3800.
- 14. (Original) The mailing form of claim 3, further comprising:

at least one area of the first side of the bottom ply including at least one closed die cut so as to produce a label on which variable information may be printed.

Claims 15 -21 (Cancelled)